




EC D Demonstration Program Participants

- Agencies
 - National
 - DOE and NREL major supporter & working group member
 - EPA review and comment on test program
 - California
 - CARB, SCAQMD and CEC are members of working group
- Academia
 - West Virginia University
 - UC Riverside
- Industry
 - Engelhard and Johnson-Matthey with support from Corning, NGK-Lock and Fleetguard Nelson
 - Cummins, Detroit Diesel, Ford and International
- Fleet operators




bp	Fuel Analysis Results 1st Round of testing Test Fuel Properties (1 Sample)			
<u>Property</u>	<u>CARB</u>	<u>ECD</u>	<u>ECD-1</u>	
Cetane Number	54.1	64.7	51.3	
Sulfur, ppm	121	7.4	13.1	
SFC Aromatics Total, vol% PNA, wt%	22.5 4.1	10.9 0.9	23.8 2.8	



LA City Refuse Haulers

- 1999 Peterbuilt 320
- Cummins L10 305 HP
- Automatic 5 speed transmission
- 58,000 lbs GVW, 40,600 lbs test weight
- Johnson Matthey CRT (continuously regenerative technology)





Mileage Accumulation

• Current Mileage Accumulation by fleet

	Ralphs	ARCO	San Diego	LA MTA
Min	125,553	112,000 *	40,249	38,400
Average	142,553	169,300	44,096	44,300
Max	156,320	239,000	47,008	50,200

* Filter removed for in lab durability testing at 112,000 miles



EC Diesel Program Summary

- 1st round emission testing illustrate PM HC & CO reduced >90%
- 2nd Round emission testing completing
 - Toxics and speciation samples collected after one year of operation samples at DRI for analysis
- Additional information (www. ecdiesel.com)
 - SAE Publications to date:
 - 2000-01-1854, 2000-01-2821, 2000-01-2815, 2001-01-0512
- CARB verification required for continued expansion of technology into market
 - Executive Orders permit sale, market demanding verification



Back Up Materials



EC D Demonstration Program Deliverables

- Emission data
 - reduction from fuel change
 - reduction from fuel change and passive regenerating particulate filters
- Toxic, speciation and sizing data
 - with and without catalyst
- Durability information
 - low sulfur/aromatic high cetane fuel
 - passive regenerating particulate filters



Emissions Test Plans


- Main Plan prepared by working group in November of 99
 - NREL, industry participants, CARB, SCAQMD, CEC, DOE
 - Reviewed by U.S. EPA
 - First round completed WVU transportable laboratory (36 vehicles)
 - Second round in process- WVU transportable laboratory
- Hertz/Ford Plan prepared by UC Riverside and working group in November 1999
- Toxic, Speciation and Particulate Sizing Plan developed
 - WVU to pull samples
 - DRI to analyze
- Double-length driving schedules were run for aftertreatmentequipped vehicles to collect enough PM
- Detection limits
 - HC = 3ppm or less (ambient), PM=0.0004 g/mile or less



San Diego School Buses

- 1998 American Transportation 3000RE / International chassis
- International 530E 8.7 liter I6 turbo, 275 hp
- Automatic transmission, 5 speed
- Engelhard DPX catalyzed soot filter
- 32,200 lb test weight








ARCO Tanker Trucks

- Kenworth chassis
- 1995 & 96 Cummins M11 10.8 litre turbocharged diesel, 330hp
- 10 spd. manual transmission
- Johnson Matthey CRT (continuously regenerative technology)
- 32,200 lb test weight







Ralphs Grocery Trucks

- Sterling L-line chassis,
- 1999 Detroit Diesel Series 60,
- 12.7 liter turbocharged diesel, 430hp
- 10 spd. manual transmission
- Johnson Matthey CRT and Engelhard DPX
- 42,000 lb test weight
- Twenty trucks tested to investigate vehicle-to-vehicle variability



